

M5012-27CK-5EU-F

APPLICATION and PERFORMANCE SPECIFICATION

Description: Standard Size - electronic low frequency square wave ballast for 50W metal halide lamps

- | | |
|---|--|
| <ul style="list-style-type: none"> • Line Voltage: 120 - 277vac , ±10%, 50/60Hz • Microprocessor controlled • RoHS Compliant • Mounting type: Feet - side lead exit | <ul style="list-style-type: none"> • Resonance Start • Active power factor correction • Abnormal operation shutdown circuit: Line voltage must be reset |
|---|--|
- 60 Hz data

Lamp		Volts	Input Watts	Nominal Line Amps	Power Factor	Ballast Factor	Harmonic Total	Crest Factor
*ANSI Type	#							
M148/M110	1	120	56	0.48	> 95%	1.00	< 10%	<1.5
	1	277	55	0.21	> 95%	1.00	< 20%	<1.5

* Consult with ULT TES engineers for lamp compatibility

Ballast Order Code: 188612

Performance:

- Meets ANSI Standard C82.14-2006
- Meets ANSI Standard C62.41-1991
- Meets FCC Part 18C for EMI & RFI (non-consumer)
- EOL Protection

Safety:

- No PCBs
- cUL_{US} Listed (Outdoor Type 1)
- Thermal Protection

Application:

- Minimum Starting Temperature: -15°C/+5°F
- Maximum Case Temperature: 80°C/ 176°F
- Sound Rated: A
- Remote Mounting: 15 feet

Each lamp's lead wires must be run in a separate minimum 1/2" ID conduit from the input leads to achieve good EMI performance and maximum remote capabilities. Individual, unbundled lead wires must be used for extension wiring using wire types SF-2 or SFF-2 or equivalent. Power cords and MC cables are not acceptable extension wiring methods.

Physical Parameters

- | | Inches/Metric |
|-------------------------------|---------------|
| • Overall Length: | 5.51"/140.0mm |
| • Width: | 3.62"/92.0mm |
| • Height: | 1.57"/39.9mm |
| • Weight: | 20 oz |
| • Lead lengths: | 10"/254mm |
| • Lead stripping:(Tinned) All | .375"/9.53mm |

Warranty:

Universal Lighting Technologies warrants to the purchaser that each electronic ballast will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. The normal operation of 4000 hr./yr. is used for the warranty period. Longer operating times will adjust the warranty period accordingly. For extended warranty periods greater than 36 months, call **1-800 BALLAST** for fixture testing instructions.

Manufactured in North America

