

Linear Pendant LPL-UD

Linkable-Switchable-Controllable | Provides maximum flexibility with full feature performance for a variety of lighting applications

EVERLINE LINEAR PENDANT LUMINAIRE

The LPL family provides an easy to install and set up pendant luminaire with high performance lighting and control features. The switchable setting allow for the installer to set 3 different power levels and 3 color temperature as well as determine the up/down lighting percentages with either all downlight or 30% and 50% uplight choices. With the switch accessible on the top side of the fixture, they are easy to change if desired. With a unique latching system, the LPL's can easily be installed and linked together for continuous, seamless runs.

In addition to the standard 0-10V control capabilities, the LPL family has field installable intelligent Bluetooth sensors and controls as options. These allow for occupancy sensing and daylight control, high-end trimming and integration with the Douglas Bluetooth lighting ecosystem of room and building controls.

Switchable Settings

- Three Power Level Settings • 4ft: 30/40/50W
- Three Up/Down Light Setting • 0/100%, 30/70%, 50/50%
- Three CCT Settings • 3000K / 3500K / 4000K

Controllable

- 0-10V Dimmable w/ Dim-to-Off
- Bluetooth Sensor and Control Options
 - Occupancy Sensing and Daylight control
 - High-End Trim and LLLC (Douglas Lighting Controls Dialog System) capabilities.
 - Integrates with other Bluetooth Dialog controls

Linkable

- 4-Foot sections can be linked together for continuous rows
- Unique Linkable bracket allows for quick and sturdy installation

Wide Range Input Voltage: 120-347V

- Power Factor <.90 at 347V



The top side has the switches for power, CCT and light distribution.

Performance

Three Selectable Power Levels

30W: 3850 Lumens

40W: 5080 Lumens

50W: 6280 Lumens

>125 Lumens Per Watt

L85 LUMEN MAINTENANCE:	>54K Hours
OPERATING TEMP RANGE:	-4° to 122°F
SOUND RATING:	A
CRI:	>80
POWER FACTOR:	>.90 except for 347V



Product Offering

- **LPL4UD-40WS835S-WRV**
 - 4-Foot Switchable Fixture
- **LPL-ACC-PCABLE**
 - Power AC Cable
 - One Required per set of fixtures linked together
 - See Spec sheet for limitations
- **LPL-ACC-LBK**
 - Linkable Bracket
 - One required to link two sections together
- **LPL-ACC-SCK**
 - Surface Canopy Kit, White Dia. 125mm
 - 1 Pair/set
- **LPL-ACC-SEC**
 - Sensor End Cap
 - Required for each BT-IFC/IFS Control that is ordered
- **BT-IFS-A**
 - Bluetooth Intelligent Fixture Sensor
- **BT-IFC-A**
 - Bluetooth Intelligent Fixture Control
- Two sets of aircraft cable (6.5ft) and mounting hardware supplied with each fixture.

UniversalDouglasSupport

Douglas Lighting Controls
(877) 873-2797
techsupport@universaldouglas.com

Universal Lighting Technologies
(800) 225-5278
tes@universaldouglas.com

universaldouglas.com

It's **EASY**
to **REACH US...**

universaldouglas.com

